







Model Code	2WD	4WD
Model Type	KJ3TENJTR	KL3TENJTR
Dimensions (mm)		
Wheelbase	3000	
Overall length	5075	
Overall width	1785	
Overall height	1655	1780
Ground clearance	200	
Weight (Kg)		
Kerb Weight	1500	1690
Gross vehicle weight	2570	2760
Engine & Transmission		
Engine model	(4D56) 2.5L 16V inline 4 (DOHC), diesel Turbocharged	
Displacement cc	2477	
Max.output (EEC net)	81 kw (110)/4,000 rpm	
Max.torque (EEC net)	200 Nm /1500-3500 rpm	
Fuel supply equipment	Electronic common rail direct injection	
Fuel tank capacity	75	
Transmission model	5 speed manual	
Steering		
Type	Rack and pinion with power assist	
Suspension		
Front	Wishbone, coil springs	
Rear	Elliptic leaf springs	
Brakes		
Front	Ventilated disc brakes (270mm)	Ventilated disc brakes (294mm)
Rear	10 inch drum brakes	11.6- inch drum brakes
Tyres & wheels		
Front and Rear	195R15C8PR Steel	205R16C8PR Steel
Perfomance		
Max. Speed (Km/h)	152	147
Min. turning radius	5.7m	5.9m

Model Code	KL3TJNJTR	KL3TJNHFR	KL3TJYHFR
Model Type	4WD GL	4WD GLS Sportero	
Dimensions (mm)			
Wheelbase	3000		
Overall length	5200		
Overall width	1785	1815	
Overall height	1775	1780	
Ground clearance	200	205	
Weight (Kg)			
Kerb Weight	1775	1820	1830
Gross vehicle weight	2850		
Engine & Transmission			
Engine model	(4D56) 2.5L 16V inline 4 (DOHC), diesel Turbocharged	(4D56) 2.5L 16V inline 4 (DOHC), intercooled Turbocharged	
Displacement cc	2477		
Max.output (EEC net)	81 kw (110)/4,000 rpm	100 kw (136)/4,000 rpm	
Max.torque (EEC net)	200 Nm/1500-3500 rpm	324Nm/2000rpm	
Fuel supply equipment	Electronic common rail direct injection		
Fuel tank capacity	75		
Transmission model	5 speed manual		5 speed AT with sports mode
Steering			
Type	Rack and pinion with power assist		
Suspension			
Front	Wishbone, coil springs		
Rear	Elliptic leaf springs		
Brakes			
Front	Ventilated disc brakes (294mm)		
Rear	11.6- inch drum brakes		
Tyres & wheels			
Front and Rear	205R16C8PR Alloy	265/70R16 Alloy	245 /65R17 Alloy
Perfomance			
Max. Speed (Km/h)	147	167	165
Min. turning radius	5.9m		

Model Code	CY1ASRSHR
Model Type	GLX 1.6 MIVEC
Dimensions (mm)	
Wheelbase	2635
Overall length	4625
Overall width	1760
Overall height	1505
Ground clearance	165
Weight (Kg)	
Kerb Weight	1225
Gross vehicle weight	1750
Engine & Transmission	
Engine model	DOHC MIVEC 16-valve (4A92)
Displacement cc	1590
Max. Output (EEC net)	86 kw (117)/6000 rpm
Max.torque (EEC net)	154 Nm/4000 rpm
Fuel supply equipment	Electonic Controlled Injection (ECI-MULTI)
Fuel tank capacity	59 lit
Transmission model	INVECS-II 4-speed automatic
Steering	
Type	Rack & Pinion power assisted
Suspensions	
Front	MacPherson strut, coil springs with stabilizer bar
Rear	Multi-link, coil springs
Brakes	
Front	Ventillated discs
Rear	Drums
Tyres & wheels	
Front and Rear	205/60R16
Performance	
Max. Speed (Km/h)	180
Min. Turning Radius	5.0m
Acceleration (0-100km/h) sec	13.6

Model Code	GA2WXTSHR
Model Type	MITSUBISHI ASX 2.0L
Dimensions (mm)	
Wheelbase	2670
Overall length	4355
Overall width	1810
Overall height	1630
Ground clearance	195
Weight (Kg)	
Kerb Weight	1355
Gross vehicle weight	1970
Engine & Transmission	
Engine model	2.0L, 16 Valve, inline 4, DOHC MIVEC, 4B11
Displacement cc	1998
Max. Output (EEC net)	110 kw (150) / 6000 rpm
Max.torque (EEC net)	197 Nm / 4200 rpm
Fuel supply equipment	Electonic Controlled Injection (ECL-MULTI)
Fuel tank capacity	63
Transmission model	INVESC.III CVT with 6 -step sports mode
Steering	
Type	Rack & Pinion with electric power assist
Suspensions	
Front	Macpherson Strut, Coil Springs with stabilizer Bar
Rear	Multi-link, Coil Springs with stabilizer Bar
Brakes	
Front	Ventilated discs
Rear	Discs
Tyres & wheels	
Front and Rear	215/60R17 (Alloy wheels)
Seating Capacity	5
Performance	
Max. Speed (Km/h)	193
Min. Turning Radius	5.3m
Acceleration (0-100km/h) sec	11.3



Model Code	GK2WXTMHR	GK2WXTHHR
Model type	ECLIPSE CROSS 2WD	
Dimensions (mm)		
Wheelbase	2670	
Overall length	4405	
Overall width	1805	
Overall height	1685	
Ground clearance	180	
Weights (Kg)		
Kerb Weight	1455	1480
Gross vehicle weight	2050	
Engine & Transmission		
Engine model	2.0-liter 16-valve DOHC MIVEC (4B11)	
Displacement cc	1998	
Max. Output (EEC net)	110 kw(150)/6000 rpm	
Max. Torque (EEC net)	198 Nm/4200 rpm	
Fuel supply equipment	Electronically controlled injection-MULTI	
Fuel tank capacity (L)	63	
Transmission	INVECS III CVT 6 step with sports mode	
Steering		
Type	Rack & Pinon with electric power assist	
Suspension		
Front	MacPherson strut with coil springs & stabilizer bar.	
Rear	Multi-link with coil springs & stabilizer bar	
Brakes		
Front	Ventilated discs	
Rear	Discs	
Tyres & wheels		
Front & Rear	215/70 R16 (Alloy wheels)	225/55 R18 (Alloy wheels)
Seating Capacity	5	
Performance		
Max. Speed (Km/h)	188	
Min. Turning Radius	5.3m	
Acceleration (0-100km/h) sec	12.1	



Model Code	GF3WXTMGZR
Model Type	OUTLANDER GLX
Dimensions (mm)	
Wheelbase	2670
Overall length	4695
Overall width	1810
Overall height	1710
Ground clearance	190
Weights (Kg)	
Kerb Weight	1535
Gross vehicle weight	2210
Engine & Transmission	
Engine model	2.4L, 16 Valve, inline 4 DOHC MIVEC, (4B12)
Displacement cc	2360
Max. Output (EEC net)	123 kw (167) / 6000 rpm
Max. Torque (EEC net)	222 Nm/4100 rpm
Fuel supply equipment	Electronically Controlled Injection
Fuel tank capacity (L)	60
Transmission	INVESC.III CVT with 6 -step sports mode
Steering	
Type	Rack & Pinon with electric power assist
Suspension	
Front	MacPherson strut with coil springs & stabilizer bar
Rear	Multi-link with coil springs & stabilizer bar
Brakes	
Front	Ventilated discs
Rear	Discs
Tyres & wheels	
Front & Rear	225/55 R18 (Alloy wheels)
Seating Capacity	7
Performance	
Max. Speed (Km/h)	198
Min. Turning Radius	5.3m
Acceleration (0-100km/h) sec	10.5



Model	KS1WGUPFPR
Model Code	Pajero Sport GLS
Dimensions (mm)	
Wheelbase	2800
Overall length	4785
Overall width	1815
Overall height	1805
Ground clearance	218
Weight (Kg)	
Kerb Weight	2030
Gross vehicle weight	2710
Engine & Transmission	
Engine model	4N15
Displacement cc	2442
Max.output (EEC net)	133 kw(180)/3500 rpm
Max.torque (EEC net)	430 Nm/2500 rpm
Fuel supply system	Electrical Fuel Injection (Common Rail)
Fuel tank capacity (L)	68
Transmission	8 speed Automatic
Steering	
Type	Rack and pinion with power steering
Suspension	
Front	Independent double wishbone, coil springs with stabilizer bar
Rear	3-link with coil springs & stabilizer bar
Brakes	
Front	Ventilated brake discs (2POT, 320mm diameter)
Rear	Ventilated brake disc
Tyres & Wheels	
Front & Rear	265/60R18(Alloy wheels)
Seating capacity	7
Perfomance	
Max. Speed (Km/h)	180
Min. turning radius	5.6m



Model Code	V96WLNXFR	V98WLYXZSR	V93WLRXVQR
Model Type	2.8 GLX Diesel	3.2 GLS Diesel	3.0L GLS Petrol
Dimensions (mm)			
Wheelbase	2780		
Overall length	4900		
Overall width	1845	1875	
Overall height	1900		
Ground clearance	235		
Weight (Kg)			
Kerb Weight	2155	2250	2105
Gross vehicle weight	2740	2865	2720
Engine & Transmission			
Engine model	(4M40) 2.8L 8V Inline 4 (SOHC) Intercooled Turbocharged	(4M41) 3.2L 16V Inline 4 (DOHC) intercooled Turbo-charged	(6G72) 3.0L 24V V6 SOHC
Displacement cc	2835	3200	2972
Max.output (EEC net)	92kw (125)/4,000 rpm	121 kw (165)/3,500rpm	135 kw (184)/ 5,250 rpm
Max.torque (EEC net)	294 Nm / 2000 rpm	373Nm / 2000 rpm	267 Nm/ 4000 rpm
Fuel supply system	Indirect fuel Injection	Electronic Common Rail Direct fuel Injection	Electronic Controlled injection (ECI- MULTI)
Fuel tank capacity (L)	88		
Transmission Model	5 speed manual	INVECS II 5 speed AT with Sports Mode	INVECS II 4 speed AT with Sports Mode
Steering			
Type	Rack and pinion with power assist		
Suspension			
Front	Double-wishbone, coil springs with stabilizer bar		
Rear	Multilink coil springs with stabilizer bar		
Brakes			
Front	Ventilated discs (2-pot)	Ventilated discs (4-pot)	Ventilated discs (2-pot)
Rear	Ventilated discs	Ventilated discs	Ventilated discs
Tyres & Wheels			
Front & Rear	265/65R17 Alloy		
Perfomance			
Max. Speed (km/h)	155	174	175
Min. turning radius	5.7m		

Available countrywide: 0703 046 000 | www.mitsubishi.co.ke | Mitsubishi Motors Kenya

Simba Corp 50 growth evolved since '68

MITSUBISHI MOTORS Drive your Ambition